

# AXIAL PRESS JOINTING

## PIPETOOLS CATALOGUE



## Axial Press Jointing

	<b>Cordless axial press 30 22V</b> <b>Compression heads</b>	<b>242</b>
	<b>Manual axial press</b>	<b>243</b>
	<b>Cordless axial press 25 22V</b> <b>Cordless axial press 25 L 22V</b>	<b>244</b>
	<b>Compression heads</b>	<b>246</b>

# REMS Ax-Press 30 22V

Cordless axial press 30 kN

Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-Ion 22V Technology. For battery and corded operation.

Axial compression  $\varnothing$  12–32 mm

**REMS Ax-Press 30 22V – up to  $\varnothing$  32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings Georg Fischer pfc ALUPEX-EXPRESS  $\varnothing$  16 mm with one battery charge\*.**

## Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system-conformity, safe jointing.

## Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads. Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

## Drive

High pressing force for perfect pressing in seconds, e.g.  $\varnothing$  26 mm in only 5 s. Thrust force 30 kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

## Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings, 4.4 Ah for approx. 380 pressings, 5.0 Ah for approx. 430 pressings, 9.0 Ah for approx. 780 pressings Georg Fischer pfc ALUPEX-EXPRESS  $\varnothing$  16 mm with one battery charge\*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

## Supply format

**REMS Ax-Press 30 22V Basic-Pack.** Cordless axial press 30 kN for producing compression sleeve joints with crimping sleeve  $\varnothing$  12–32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V, 50–60Hz, 70W. In sturdy steel case.

	Art.-No.
	573018

## Accessories

Description	Art.-No.
<b>REMS Ax-Press 30 22V drive unit, without battery</b>	573008
<b>Battery Li-Ion 21.6V, 2.5 Ah</b>	571571
<b>Battery Li-Ion 21.6V, 4.4 Ah</b>	571574
<b>Battery Li-Ion 21.6V, 5.0 Ah</b>	571581
<b>Battery Li-Ion 21.6V, 9.0 Ah</b>	571583
<b>Rapid charger 100–240V, 50–60Hz, 90W</b>	571585
<b>Rapid charger 100–240V, 50–60Hz, 290W</b>	571587
<b>Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V.</b>	571567
<b>Steel case with insert</b>	573282
<b>REMS Lumen 2800 22V, cordless LED flood light, see page 111</b>	

## REMS compression heads

Compression sleeve system	Compression head	Art.-No.
<b>Brasstech Raptor/ Metalpex/ Raptor 2/ MULTitermoSAN</b>	ME 14 (pack of 2)	573100
	ME 16 (pack of 2)	573102
	ME 20 (pack of 2)	573106
	ME 26 (pack of 2)	573108
	ME 32 (pack of 2)	573110
<b>General Fittings Serie 5400</b>	ME 14 (pack of 2)	573100
	ME 16 (pack of 2)	573102
	ME 20 (pack of 2)	573106
	ME 26 (pack of 2)	573108
	ME 32 (pack of 2)	573110



e.g.  
Brasstech,  
General Fittings,  
Georg Fischer pfc

German Quality Product



## REMS compression heads

Compression sleeve system	Compression head	Art.-No.
<b>Georg Fischer pfc ALUPEX-EXPRESS/ Alupex Gas System</b>	ME 16 (pack of 2)	573102
	ME 20 (pack of 2)	573106
	ME 26 (pack of 2)	573108
<b>Logstor</b>	ME 16 (pack of 2)	573102
	LR 20 (pack of 2)	573430
	LR 22 (pack of 2)	573432
	LR 25 (pack of 2)	573434
	LR 28 (pack of 2)	573436
	LR 32 (pack of 2)	573438



Universal manual axial press for producing compression sleeve joints.

Axial compression Ø 12 – 32 mm

**REMS Ax-Press HK – universal up to Ø 22 mm**  
Ultra small, ultra light, ultra handy. Only 1.1 kg

**REMS Ax-Press H – universal up to Ø 32 mm.**  
Handy and light. Only 1.4 kg.

**Complete assortment of REMS compression heads, quickly interchangeable.**

### System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

### Compression heads

Full range of REMS compression heads for all common compression sleeve systems (page 246–247). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

### Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 246). No need to change compression heads. Extremely simple, saves time.

### Design

Compact, job site proven. Handy and light. REMS Ax-Press HK drive unit only 1.1 kg. REMS Ax-Press H drive unit only 1.4 kg. Works anywhere, free-hand, also in tight spots. 66 mm stroke. Quick-acting forward and release for easy, fast operation. Selectable compression head position (**Patent DE 10 2004 018 429, Patent ES 2 273 563, Patent FR 05 03513**) for pressing compression sleeve connectors with a clamping distance of ≤ 161 mm in one action and for double pressings. Quick-change compression heads and pressing inserts without tools. Secure fit of compression heads and pressing inserts by spring catch. REMS Ax-Press H with overload protection.

### Expanding

Various pipe expanders and complete range of REMS expanding heads for all common compression sleeve systems (page 251–255).



### Supply format

**REMS Ax-Press HK drive unit.** Axial press for single-handed operation for producing compression sleeve joints Ø 12–22 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	
	574302	

### Supply format

**REMS Ax-Press H drive unit.** Manual axial press for producing compression sleeve joints Ø 12–32 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	
	574300	

### Accessories

Description	Art.-No.	
<b>REMS compression heads</b> see page 246–247.		
<b>Carrying bag</b> for REMS Ax-Press HK/H drive unit and compression heads	574437	
<b>Case</b> with inlay for REMS Ax-Press HK drive unit and compression heads	574352	

German Quality Product



## REMS Ax-Press 25 22V ACC REMS Ax-Press 25 L 22V ACC

Cordless axial press 20 kN with automatic return  
Cordless axial press 13 kN with automatic return

Compact, handy power tool with automatic return for manufacturing compression sleeve joints. Li-Ion 22V Technology. For battery and corded operation. For trade and industry. For the building site and the workshop.

Axial compression  $\varnothing$  12 – 40 mm

**REMS Ax-Press 25 22V ACC – universal up to  $\varnothing$  40 mm. Super light, super handy. Fast. With automatic return. Optimum weight distribution for single-hand operation. Swivelling compression device. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings REHAU RAUTITAN PX  $\varnothing$  16 mm with one battery charge\*.**

### System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

### Compression heads for all common systems

Full range of REMS compression heads for all common compression sleeve systems (page 246 – 247). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

### Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 246). No need to change compression heads. Extremely simple, saves time.

### Design

Compact, handy, light. REMS Ax-Press 25 22V ACC drive machine with battery weighs only 3.0 kg, only 28 cm long REMS Ax-Press 25 L 22V ACC drive machine with battery weighs only 3.2 kg, only 31 cm long REMS Ax-Press 25 22V ACC and REMS Ax-Press 25 L 22V ACC with 40 mm stroke respectively REMS Ax-Press 25 22V ACC with preset compression head position for pressing compression sleeve connectors with a clamping distance  $a \leq 82$  mm in one action REMS Ax-Press 25 L 22V ACC with selectable compression head position for pressing compression sleeve connectors with a clamping distance  $a \leq 116$  mm in one action and for double pressings. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. LED work light for illuminating the work place. Swivelling compression device for working in confined area. Compression heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

### Drive

Enormous pressing force for fast and perfect jointing. Thrust force REMS Ax-Press 25 22V 20 kN, thrust force REMS Ax-Press 25 L 22V 13 kN. Powerful electro-hydraulic drive with automatic return (ACC), eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

### Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings, 4.4 Ah for approx. 880 pressings, 5.0 Ah for approx. 1000 pressings, 9.0 Ah for approx. 1800 pressings REHAU RAUTITAN PX  $\varnothing$  16 mm with one battery charge\*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240V, 90W. Rapid charger 100 – 240V, 290W, for shorter charging times, as accessory. Voltage supply 220 – 240V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

### Expanding

Various pipe expanders and complete range of REMS expanding heads for all common pressure sleeve systems

REMS Ax-Press 25 22V ACC



←ACC→  
Automatic Circuit Control

with automatic circuit control  
and charging status check

e.g.  
aquatherm,  
General Fittings,  
IVT,  
REHAU,  
REVEL,  
Seppelfricke,  
TECE,  
TIEMME,  
Würth

REMS TECHNOLOGY  
LI-ION 22V

REMS Ax-Press 25 L 22V ACC




←ACC→  
Automatic Circuit Control

with automatic circuit control  
and charging status check

e.g.  
AC-FIX,  
BARBI,  
FERRO systems  
BRASELI,  
Brass & Fittings,  
EUROP'FLUIDES,  
Fittings Estándar,  
PLÁSTICOS FERRO,  
Velta

REMS TECHNOLOGY  
LI-ION 22V

German Quality Product



### Supply format

**REMS Ax-Press 25 22 V ACC Basic-Pack.** Cordless axial press 20 kN for producing compression sleeve joints Ø 12 – 40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance  $a \leq 82$  mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	
	573022	

Other voltages on request.



Info

### Supply format

**REMS Ax-Press 25 L 22 V ACC Basic-Pack.** Cordless axial press 13 kN for producing compression sleeve joints Ø 12 – 40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance  $a \leq 116$  mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	
	573023	

Other voltages on request.



Info


### Accessories

Description	Art.-No.	
<b>REMS compression heads</b> see page 246 – 247.		
<b>REMS Ax-Press 25 22 V ACC drive unit,</b> a ≤ 82 mm, without battery	573020	
<b>REMS Ax-Press 25 L 22 V ACC drive unit,</b> a ≤ 116 mm, without battery	573021	
<b>Battery Li-Ion 21.6 V, 2.5 Ah</b>	571571	
<b>Battery Li-Ion 21.6 V, 4.4 Ah</b>	571574	
<b>Battery Li-Ion 21.6 V, 5.0 Ah</b>	571581	
<b>Battery Li-Ion 21.6 V, 9.0 Ah</b>	571583	
<b>Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W</b>	571585	
<b>Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W</b>	571587	
<b>Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A,</b> for mains operation instead of battery Li-Ion 21.6 V.	571567	
<b>Steel case with insert</b>	578290	
<b>REMS Lumen 2800 22 V,</b> cordless LED flood light, see page 111		



# REMS compression heads

Accessories for REMS Ax-Press HK, REMS Ax-Press H,  
REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC



## REMS compression heads with spring lock for commercially available press inserts

Description	Use
<b>Compression head Basic 20</b> (pack of 2)	for pipe fittings 20 mm and for standard press inserts outer Ø 20 mm
<b>Compression head Basic 25</b> (pack of 2)	for pipe fittings 25 mm and for standard press inserts outer Ø 25 mm
<b>Compression head Basic 32</b> (pack of 2)	for pipe fittings 32 mm and for standard press inserts outer Ø 32 mm



## REMS twin compression heads

Description	Use
<b>Twin compression head RH 16/20</b> (pack of 2)	for pipe fittings 16 and 20 mm



## REMS compression head for T-pieces, elbows, splitters, transition pieces

Description	Use
<b>Compression head UNI T/L</b> (piece)	for T-pieces, elbows, splitters, in combination with an additional compression head; for transition pieces, in combination with a support bol



## REMS support bolt for transition pieces

Description	for transition pieces inch	Art.-No.	
<b>Support bolt 3/8"</b>	3/8	573647	
<b>Support bolt 1/2"</b>	1/2	573648	
<b>Support bolt 3/4"</b>	3/4	573649	

Commercially available  
press inserts:

T's and  
elbows


Dm 16

Dm 20

Dm 22

Dm 25

Dm 32






# REMS compression heads

## Select compression heads yourself!

Search for the required compression sleeve system in the table below and select the correct compression heads.


High-grade compression heads in forged and specially hardened steel. Quickly interchangeable, without tools. The REMS compression heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, safe jointing. Drive through REMS axial presses.



Compr. heads Uni



Compr. head UNI T/L



Compr. heads Basic for press inserts

Pressure sleeves system	Compression head mm	Number of pressing heads	fits REMS Ax-Press				Art.-No.
			HK <sup>1)</sup>	H	25	25L	
AC-FIX (Global Piping System)	UNI 12	2	•	•	•	•	573630
	UNI 16	2	•	•	•	•	573632
	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI T/L**	1	•	•	•	•	573646
	Basic 20*	2	•	•	•	•	573624
	Basic 25*	2	•	•	•	•	573616
aquatherm	AT 16	2	•	•	•	•	573120
	AT 20	2	•	•	•	•	573122
	AT 25	2	•	•	•	•	573124
	AT 32	2	•	•	•	•	573126
	AT 40	2	•	•	•	•	573128
	UNI 18	2	•	•	•	•	573634
	UNI 22	2	•	•	•	•	573638
	UNI 26	2	•	•	•	•	573642
BARBI GLADIATOR (Industrial Blansol)	UNI 32	2	•	•	•	•	573644
	UNI 40	2	•	•	•	•	573652
	UNI T/L**	1	•	•	•	•	573646
	Basic 20*	2	•	•	•	•	573624
	Basic 25*	2	•	•	•	•	573616
	Basic 32*	2	•	•	•	•	573628
	UNI 12	2	•	•	•	•	573630
	UNI 16	2	•	•	•	•	573632
BARBI RETICULADO (Industrial Blansol)	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI 40	2	•	•	•	•	573652
	UNI T/L**	1	•	•	•	•	573646
	Basic 20*	2	•	•	•	•	573624
	Basic 25*	2	•	•	•	•	573616
	Basic 32*	2	•	•	•	•	573628
FERRO systems BRASELI GPF AXIAL	UNI 12	2	•	•	•	•	573630
	UNI 16	2	•	•	•	•	573632
	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI T/L**	1	•	•	•	•	573646
	Basic 20*	2	•	•	•	•	573624
	Basic 25*	2	•	•	•	•	573616
Brass & Fittings PRESSMAN PowerFit	Basic 32*	2	•	•	•	•	573628
	UNI 16	2	•	•	•	•	573632
	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI T/L**	1	•	•	•	•	573646
	Basic 20*	2	•	•	•	•	573624
	Basic 25*	2	•	•	•	•	573616
COMAP PEXY	Basic 32*	2	•	•	•	•	573628
	UNI 12	2	•	•	•	•	573630
	UNI 16	2	•	•	•	•	573632
	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI T/L**	1	•	•	•	•	573646
	Basic 25*	2	•	•	•	•	573616
EUROP' FLUIDES HYDROFLUIDES	Basic 32*	2	•	•	•	•	573628
	UNI 12	2	•	•	•	•	573630
	UNI 16	2	•	•	•	•	573632
	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI T/L**	1	•	•	•	•	573646
	Basic 25*	2	•	•	•	•	573616
Fittings Estándar	Basic 32*	2	•	•	•	•	573628
	UNI 12	2	•	•	•	•	573630
	UNI 16	2	•	•	•	•	573632
	UNI 20	2	•	•	•	•	573636
	UNI 25	2	•	•	•	•	573640
	UNI 32	2	•	•	•	•	573644
	UNI T/L**	1	•	•	•	•	573646
	Basic 20*	2	•	•	•	•	573624
General Fittings Serie 3400 PEX Gold-Fix	Basic 25*	2	•	•	•	•	573616
	Basic 32*	2	•	•	•	•	573628
	RE 16	2	•	•	•	•	573160
	RE 20	2	•	•	•	•	573162
	RE 25	2	•	•	•	•	573172
	RE 32	2	•	•	•	•	573178
	RO 16	2	•	•	•	•	573184
	RO 20	2	•	•	•	•	573186
General Fittings Serie 3400 PEX/AL/PEX Gold-Fix	RE 16	2	•	•	•	•	573160
	RE 20	2	•	•	•	•	573162
	RE 25	2	•	•	•	•	573172
	RE 32	2	•	•	•	•	573178
	RO 16	2	•	•	•	•	573184
	RO 20	2	•	•	•	•	573186
	TC 12/14/16	2	•	•	•	•	573360
	TC 18/20	2	•	•	•	•	573364
General Fittings Serie 3700 PEX	TC 25	2	•	•	•	•	573367
	TC 32	2	•	•	•	•	573370
	TC 12/14/16	2	•	•	•	•	573360
	TC 18/20	2	•	•	•	•	573364
	TC 25	2	•	•	•	•	573367
	TC 32	2	•	•	•	•	573370
	HERZ QUICK FIX	2	•	•	•	•	573112
	HC 20	2	•	•	•	•	573114
IVT PRINETO	HC 26	2	•	•	•	•	573116
	HC 32	2	•	•	•	•	573118
	IV 16/17	3	•	•	•	•	573320
	IV 20/21	3	•	•	•	•	573325
	IV 25/26	3	•	•	•	•	573330
	IV 32/33	3	•	•	•	•	573335

Accessories for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC

Pressure sleeves system	Compression head mm	Number of pressing heads	fits REMS Ax-Press				Art.-No.
			HK <sup>1)</sup>	H	25	25L	
PB TUB Sertiglass	UNI 12	2	•	•			573630
	UNI 16	2	•	•			573632
	UNI 20	2	•	•			573636
	UNI 25	2		•			573640
	UNI 32	2		•			573644
	UNI T/L**	1	•	•			573646
	Basic 25* Basic 32*	2 2	• •	• •			573616 573628
PLÁSTICOS FERRO FERROPLAST GPF AXIAL	UNI 16	2	•	•		•	573632
	UNI 20	2	•	•		•	573636
	UNI 25	2		•		•	573640
	UNI 32	2		•		•	573644
	UNI T/L**	1	•	•		•	573646
	Basic 20* Basic 25* Basic 32*	2 2 2	• • •	• • •		• • •	573624 573616 573628
	PLUMBING PLUS EZIPEX Sleeve Water (AUS)	RH 16 L	2				•
RH 20 L		2				•	573152
RH 16/20 L		2				•	573158
RH 25		2				•	573154
RH 32		2				•	573156
PLUMBING PLUS EZIPEX Sleeve Gas (AUS)	RH 16 L	2				•	573150
	RH 20 L	2				•	573152
	RH 16/20 L	2				•	573158
	RH 25	2				•	573154
	RH 32	2				•	573156
REHAU RAUTHERM SDR 11 LX	RH 12	2				•	573164
	RH 16	2				•	573166
	RH 20	2				•	573170
	RH 25	2				•	573154
	RH 32	2				•	573156
REHAU RAUTHERM S (REHAU HAS)	RH 17	2				•	573168
	RH 20	2				•	573170
	RH 25	2				•	573154
	RH 32	2				•	573156
REHAU RAUTITAN PX/MX/SX/RX/ gas/sprinkler	RE 16	2				•	573160
	RE 20	2				•	573162
	RE 25	2				•	573172
	RE 32	2				•	573178
	RE 40	2				•	573176
REHAU (GBR) EVERLOC	RH 16	2				•	573166
	RH 20	2				•	573170
	RH 25	2				•	573154
	RH 32	2				•	573156
REVEL-PEX	RV 16	2		•	•	•	573400
	RV 20	2		•	•	•	573402
	RV 25	2		•	•	•	573404
	RV 32	2				•	573406
REVI REVIUNI	TC 12/14/16	2			•		573360
	TC 18/20	2			•		573364
	TC 25	2			•		573367
	TC 32	2			•		573370
REVI REVITERM	TC 12/14/16	2			•		573360
Riquier à glissement	UNI 12	2	•	•			573630
	UNI 16	2	•	•			573632
	UNI 20	2	•	•			573636
	UNI 25	2		•			573640
	UNI 32	2		•			573644
	UNI T/L**	1	•	•			573646
	Basic 25*	2	•	•			573616
Seppelfricke SD Sistemi Italia Sylver	RE 16	2				•	573160
	RE 20	2				•	573162
	RE 25	2				•	573172
	RE 32	2				•	573178
	RO 16	2				•	573184
	RO 20	2				•	573186
Seppelfricke SD Sistemi Italia Neroflex	RE 16	2				•	573160
	RE 20	2				•	573162
	RE 25	2				•	573172
	RE 32	2				•	573178
	RO 16	2				•	573184
	RO 20	2				•	573186
TECE TECEflex	TC 12/14/16	2	•	•	•		573360
	TC 18/20	2	•	•	•		573364
	TC 25	2		•	•		573367
	TC 32	2		•	•		573370
TIEMME Assialpex	RE 16	2		•	•		573160
	RE 20	2		•	•		573162
	RE 25	2		•	•		573172
	RE 32	2		•	•		573178
Tradelink TradePex Sleeve Water	RH 16 L	2				•	573150
	RH 20 L	2				•	573152
	RH 16/20 L	2				•	573158
	RH 25	2				•	573154
	RH 32	2				•	573156
Tradelink TradePex Sleeve Gas	RH 16 L	2				•	573150
	RH 20 L	2				•	573152
	RH 16/20 L	2				•	573158
	RH 25	2				•	573154
	RH 32	2				•	573156
Velta Eurojauge	UNI 12	2	•	•		•	573630
	UNI 16	2	•	•		•	573632
	UNI 20	2	•	•		•	573636
	UNI 25	2		•		•	573640
	UNI T/L**	1	•	•		•	573646
	Basic 25*	2	•	•		•	573616
Würth PRINETO	IV 16/17	3				•	573320
	IV 20/21	3				•	573325
	IV 25/26	3				•	573330
	IV 32/33	3				•	573335